

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
25 September 2003 (25.09.2003)

PCT

(10) International Publication Number
WO 03/079390 A1

(51) International Patent Classification: H01H 85/143

(21) International Application Number: PCT/KR03/00503

(22) International Filing Date: 14 March 2003 (14.03.2003)

(25) Filing Language: Korean

(26) Publication Language: English

(30) Priority Data:
10-2002-0014230 15 March 2002 (15.03.2002) KR

(71) Applicant (for all designated States except US): ALPI CO., LTD. [KR/KR]; 1070-7 Hogyeo-dong, Dongan-gu, Anyang-city 431-080 (KR).

(72) Inventor; and

(75) Inventor/Applicant (for US only): KIM, Chang-II [KR/KR]; 1454-5 Kwanyang-dong, Dongan-gu, Anyang-city 431-060 (KR).

(74) Agent: LIM, Young-Hee; Sinmyong Bldg., 3rd Floor, 645-21 Yoksam-dong, Kangnam-ku, Seoul 135-080 (KR).

(81) Designated States (national): AE, AG, AI, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD OF PRODUCING FUSES



(57) Abstract: A method is provided for producing fuses with an increased yield rate and in a highly automated fashion. The method comprises the steps of processing a metal sheet into a blank having a plurality of continuously distributed pairs of lead conductors, molding an insulator base integrally with each pair of the lead conductors, electrically interconnecting the lead conductors of the respective conductor pair with a fusible connector, and severing the lead conductors from the blank. Additionally, a protection cap is coupled to the insulator base in such a manner that the cap can enclose the fusible connector in its entirety.

WO 03/079390 A1